

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI-CATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		5. LEASE DESIGNATION AND SERIAL NO.
2. NAME OF OPERATOR		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR The Eastland Oil Company		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660 feet FNL and 660 feet P.L.		8. FARM OR LEASE NAME
14. PERMIT NO.		9. WELL NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3573' GR, 3,663' DF (ref.)		10. FIELD AND POOL, OR WILDCAT
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., TWP., R. OR B.L. AND SURVEY OR AREA
		12. COUNTY OR PARISH
		13. STATE

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☒ Casing setting	
(Other) ☐		(NOTE: Report results of multiple completion or well completion or recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11" hole at 7:30 p.m. March 16, 1971 and drilled to 700 feet in anhydrite. Ran 17 joints 1, 2, 3-5/8" casing, 686 feet, set at 677 feet. Cemented with 350 sacks Class "C", 20 bag/lb. Cement in place at 9:30 p.m., March 17, 1971. Circulated out approximately 50 sacks excess cement.

Allowed cement to set 12 hours. Wippled up and tested 3-5/8" casing with 800 psi for 30 minutes with no pressure leak-off. Drilled cement plug at 1:00 p.m., March 18, 1971.

RECEIVED
MAR 26 1971
O. C. C.
ARTESIA, OFFICE

RECEIVED
MAR 22 1971
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Vice President DATE March 19, 1971

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE District Engineer DATE

CONDITIONS OF APPROVAL IF ANY:

ACCEPTED FOR RECORD PURPOSE
MAR 25 1971
Date
ACTING [Signature] District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

16-47-485

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

REPORTS AND RECORDS ON WELLS