

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 27 1971

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Jones D
9. Well No. 5
10. Field and Pool, or Wildcat Undesignated
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-
2. Name of Operator Kewanee Oil Company
3. Address of Operator P. O. Box 3786, Odessa, Texas 79760
4. Location of Well UNIT LETTER L 2310 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 18 TOWNSHIP 18S RANGE 27E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3285' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded with rotary tools 5-18-71. Drilled 11" hole to 1006' G.L. Cemented 8-5/8", 24#, K, new API casing at 1004.76' G.L. with 400 sacks 50-50 Pozmix with 2% gel, 2% CaCl₂ and 100 sacks Class C Neat with 2% CaCl₂. Circulated cement to surface. WOC 18 hours. Drilled shoe, tested cement to 300 psi, lost 20 psi in 30 minutes.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>David C. Newman</i></u>	TITLE Division Engineer	DATE 5-26-71
APPROVED BY <u><i>W. A. Gressett</i></u>	TITLE <u><i>W. A. Gressett</i></u>	DATE MAY 27 1971

CONDITIONS OF APPROVAL, IF ANY: