

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0334702

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR The Eastland Oil Company	8. FARM OR LEASE NAME Allied Federal
3. ADDRESS OF OPERATOR 704 Western United Life Building, Midland, Texas 79701	9. WELL NO. One (1)
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' from South line, 660' from West line.	10. FIELD AND POOL, OR WILDCAT Undesignated
14. PERMIT NO.	11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Section 31, 7-18-S, 2-31-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3606' GR; 3616' DF.	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Casing setting(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11" hole at 5:00 p.m., June 29, 1971 and drilled to 661' in anhydrite. Ran 16 joints #1, 20#, 3-5/8" casing; 649.58', set at 661'. Cemented with 350 sacks Class "C", 2% CaCl₂. Cement in place at 7:00 p.m., June 30, 1971. Circulated out approximately 30 sacks excess cement.

Allowed cement to set 12 hours. Hipped up and tested 3-5/8" casing with 800 psi for 30 minutes with no pressure leak-off. Drilled cement plug at 2:00 p.m., July 1, 1971.

RECEIVED

JUL 9 1971

O. C. C.
ARTESIA, OFFICE

RECEIVED

JUL 8 1971

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

George D. Neal

TITLE

Vice President

DATE

July 7, 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES
JUL - 8 1971
Date
ACTING District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.