

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-047633(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sibyl Federal

9. WELL NO.

Two (2)

10. FIELD AND POOL, OR WILDCAT

Undesignated11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Section 1,****T-18-S, R-30-E**

12. COUNTY OR PARISH 13. STATE

Eddy**New Mexico**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

The Eastland Oil Company

3. ADDRESS OF OPERATOR

704 Western United Life Building, Midland, Texas 797014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**1650' from North line and 330' from East line.**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3580' GR; 3590' RT

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**casing setting** ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

On August 19, 1971 spudded 11" hole with rotary rig at 6:00 p.m. and drilled to 675 feet in anhydrite. Ran 19 joints #1, 20#, 8-5/8" casing, 659', set at 671'. Cemented with 350 sacks Class "C" cement with 2% CaCl₂. Cement was in place at 2:00 p.m. August 20. Allowed cement to set 12 hours and nipples up and tested casing with 800 psi for 30 min. with no pressure leak-off. Drilled cement plug at 6:00 a.m. August 21, 1971.

RECEIVED

AUG 25 1971

O. C. C.
ARTESIA, OFFICE

RECEIVED

AUG 24 1971

18. I hereby certify that the foregoing is true and correct

SIGNED George D. NealTITLE Vice PresidentDATE August 23, 1971

(This space for Federal or State office use)

TITLE _____

DATE _____

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AUG 24 1971
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.