

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

Jim Knauf - 6-4138

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Reading & Bates Inc.</i>		Lease <i>Linck</i>		Well # <i>1</i>	
Location of Well	Unit <i>17803+W</i>	Section <i>24</i>	Township <i>18</i>	Range <i>25</i>	County <i>Elddy</i>
Drilling Contractor <i>Jack Leach Cusher</i> <i>McVay -</i>	Type of Equipment <i>Rotary</i>				
APPROVED CASING PROGRAM <i>4P 11-3-71</i> <i>Don Kipper</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17</i>	<i>13 3/8"</i>	<i>48</i>		<i>500</i>	<i>500 Cmc.</i>
<i>12 3/4</i>	<i>8 5/8"</i>	<i>24</i>		<i>1200</i>	<i>550 "</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>11.60</i>		<i>9000</i>	<i>500 to 6000</i>
Casing Data: <i>13 3/8" - 487 DF - 600 Cmc. 1825x, PD @ 12:30 AM 11-4-71</i>					
Surface <i>43</i> joints of <i>8 5/8"</i> inch <i>24</i> # Grade <i>K-5 ST.C New API</i>					
(Approved) (Rejected)					
Inspected by <i>Gressett</i>			date <i>11-5-71</i>		
Cementing Program					
Size of hole	Size of Casing	Sacks cement required			
Type of Shoe used	Float collar used	Btm 3 jts welded			
TD of hole	Set	Feet of	Inch	# Grade	
New-used csq. @ with sacks neat cement around shoe					
+ sax additives					
Plug down @ (AM) (PM) Date					
Cement circulated No. of Sacks					
Cemented by Witnessed by					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>CC 675</i>					

