

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED NEW MEXICO OIL CONSERVATION COMMISSION

NOV 8 1971

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Reading & Bates, Inc.		8. Farm or Lease Name Linck
3. Address of Operator 810 East County Road, Room 202, Odessa, Texas 79760		9. Well No. 1
4. Location of Well UNIT LETTER K , 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 18S RANGE 35E NMPM.		10. Field and Pool, or Wildcat West Atoka Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3460 GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>		COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded 17½" hole @ 12 Noon 11-3-71
 Drilled to TD of 487', ran 17 jts. 13 3/8" 48# H-40 Casing (497')
 Cemented with 400 sax Halliburton Light Cement w/5# Gilsonite & 1/2# Flocele per sack &
 2% CC, followed by 100 sax Class C Cement w/2% CC, Cement circulated.
 Plug down @ 12:30 A.M. 11-4-71.
 Will drill out @ 6:30 P.M. 11-4-71.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u><i>Robert J. Kuyper</i></u>	TITLE <u>Field Supervisor</u>	DATE <u>11-4-71</u>
APPROVED BY <u><i>W. A. Gressett</i></u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>NOV 15 1971</u>
CONDITIONS OF APPROVAL, IF ANY:		