

FLUID SAMPLER DATA				Date 12-4-71		Ticket Number 431438																																																																																																																																																																					
Sampler Pressure 250 P.S.I.G. at Surface Recovery: Cu. Ft. Gas 2.70 cc. Oil _____ cc. Water _____ cc. Mud _____ Tot. Liquid cc. _____				Kind of Job OPEN HOLE		Halliburton District ARTESIA																																																																																																																																																																					
				Tester MR. MURDOCK		Witness MR. BROOKS																																																																																																																																																																					
Gravity _____ ° API @ _____ °F.				Drilling Contractor MC VEY DRILLING COMPANY BC S																																																																																																																																																																							
Gas/Oil Ratio _____ cu. ft./bbl.				EQUIPMENT & HOLE DATA																																																																																																																																																																							
RESISTIVITY Recovery Water _____ @ _____ °F. _____ ppm Recovery Mud _____ @ _____ °F. _____ ppm Recovery Mud Filtrate _____ @ _____ °F. _____ ppm Mud Pit Sample _____ @ _____ °F. _____ ppm Mud Pit Sample Filtrate _____ @ _____ °F. _____ ppm Mud Weight 9.2 vis 48 cp CHLORIDE CONTENT _____ ppm				Formation Tested Morrow																																																																																																																																																																							
				Elevation 3474' KB Ft.																																																																																																																																																																							
				Net Productive Interval 18' Ft.																																																																																																																																																																							
				All Depths Measured From 14' Rotary Table																																																																																																																																																																							
				Total Depth 8880' Ft.																																																																																																																																																																							
				Main Hole/Casing Size 7 7/8"																																																																																																																																																																							
				Drill Collar Length 737' I.D. 2.25"																																																																																																																																																																							
				Drill Pipe Length 7900' I.D. 3.826"																																																																																																																																																																							
				Packer Depth(s) 8754' - 8760' Ft.																																																																																																																																																																							
				Depth Tester Valve 8723' Ft.																																																																																																																																																																							
TYPE		AMOUNT		Depth Back Pres. Valve		Surface Choke																																																																																																																																																																					
Cushion						1" ADJ. Bottom Choke 3/4"																																																																																																																																																																					
Recovered		340		Feet of Drilling mud																																																																																																																																																																							
Recovered				Feet of																																																																																																																																																																							
Recovered				RECEIVED																																																																																																																																																																							
Recovered				Feet of																																																																																																																																																																							
Recovered				Feet of																																																																																																																																																																							
Recovered				Feet of																																																																																																																																																																							
Remarks See production test data sheet.																																																																																																																																																																											
CHARTS INDICATE PARTIAL PLUGGING OF ANCHOR PERFORATIONS DURING FIRST FLOW PERIOD.																																																																																																																																																																											
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">TEMPERATURE</th> <th colspan="2">Gauge No. 1920</th> <th colspan="2">Gauge No. 1919</th> <th colspan="2">Gauge No.</th> <th colspan="2" rowspan="2">TIME</th> </tr> <tr> <th>Depth:</th> <th></th> <th>Depth:</th> <th></th> <th>Depth:</th> <th></th> </tr> </thead> <tbody> <tr> <td></td> <td>8741</td> <td>Ft.</td> <td>8876</td> <td>Ft.</td> <td></td> <td>Ft.</td> <td></td> <td></td> </tr> <tr> <td></td> <td>24</td> <td>Hour Clock</td> <td>24</td> <td>Hour Clock</td> <td></td> <td>Hour Clock</td> <td></td> <td></td> </tr> <tr> <td>Est. °F.</td> <td>Blanked Off</td> <td>No</td> <td>Blanked Off</td> <td>Yes</td> <td>Blanked Off</td> <td></td> <td>Tool Opened</td> <td>3:00 A.M. P.M.</td> </tr> <tr> <td>Actual 154°F.</td> <td colspan="2">Pressures</td> <td colspan="2">Pressures</td> <td colspan="2">Pressures</td> <td>Tool Closed</td> <td>10:30 A.M. P.M.</td> </tr> <tr> <td></td> <td>Field</td> <td>Office</td> <td>Field</td> <td>Office</td> <td>Field</td> <td>Office</td> <td>Reported</td> <td>Computed</td> </tr> <tr> <td>Initial Hydrostatic</td> <td>UTR</td> <td>4269</td> <td>4298</td> <td>4326</td> <td></td> <td></td> <td>Minutes</td> <td>Minutes</td> </tr> <tr> <td rowspan="2">First Period Flow</td> <td>Initial</td> <td>115</td> <td>120</td> <td>466</td> <td>471</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Final</td> <td>184</td> <td>192</td> <td>442</td> <td>478</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Closed in</td> <td>3171</td> <td>3211</td> <td>3149</td> <td>3186</td> <td></td> <td>30</td> <td>29</td> </tr> <tr> <td rowspan="2">Second Period Flow</td> <td>Initial</td> <td>207</td> <td>150</td> <td>233</td> <td>212</td> <td></td> <td>60</td> <td>60</td> </tr> <tr> <td>Final</td> <td>230</td> <td>236</td> <td>233</td> <td>249</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Closed In</td> <td>3401</td> <td>3397</td> <td>3379</td> <td>3372</td> <td></td> <td>120</td> <td>121</td> </tr> <tr> <td rowspan="2">Third Period Flow</td> <td>Initial</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>240</td> <td>240</td> </tr> <tr> <td>Final</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Closed In</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Final Hydrostatic</td> <td>4271</td> <td>4253</td> <td>4275</td> <td>4287</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="7">UTR + Unable to read</td> </tr> </tbody> </table>								TEMPERATURE	Gauge No. 1920		Gauge No. 1919		Gauge No.		TIME		Depth:		Depth:		Depth:			8741	Ft.	8876	Ft.		Ft.				24	Hour Clock	24	Hour Clock		Hour Clock			Est. °F.	Blanked Off	No	Blanked Off	Yes	Blanked Off		Tool Opened	3:00 A.M. P.M.	Actual 154°F.	Pressures		Pressures		Pressures		Tool Closed	10:30 A.M. P.M.		Field	Office	Field	Office	Field	Office	Reported	Computed	Initial Hydrostatic	UTR	4269	4298	4326			Minutes	Minutes	First Period Flow	Initial	115	120	466	471				Final	184	192	442	478					Closed in	3171	3211	3149	3186		30	29	Second Period Flow	Initial	207	150	233	212		60	60	Final	230	236	233	249					Closed In	3401	3397	3379	3372		120	121	Third Period Flow	Initial						240	240	Final									Closed In								Final Hydrostatic	4271	4253	4275	4287						UTR + Unable to read						
TEMPERATURE	Gauge No. 1920		Gauge No. 1919		Gauge No.		TIME																																																																																																																																																																				
	Depth:		Depth:		Depth:																																																																																																																																																																						
	8741	Ft.	8876	Ft.		Ft.																																																																																																																																																																					
	24	Hour Clock	24	Hour Clock		Hour Clock																																																																																																																																																																					
Est. °F.	Blanked Off	No	Blanked Off	Yes	Blanked Off		Tool Opened	3:00 A.M. P.M.																																																																																																																																																																			
Actual 154°F.	Pressures		Pressures		Pressures		Tool Closed	10:30 A.M. P.M.																																																																																																																																																																			
	Field	Office	Field	Office	Field	Office	Reported	Computed																																																																																																																																																																			
Initial Hydrostatic	UTR	4269	4298	4326			Minutes	Minutes																																																																																																																																																																			
First Period Flow	Initial	115	120	466	471																																																																																																																																																																						
	Final	184	192	442	478																																																																																																																																																																						
	Closed in	3171	3211	3149	3186		30	29																																																																																																																																																																			
Second Period Flow	Initial	207	150	233	212		60	60																																																																																																																																																																			
	Final	230	236	233	249																																																																																																																																																																						
	Closed In	3401	3397	3379	3372		120	121																																																																																																																																																																			
Third Period Flow	Initial						240	240																																																																																																																																																																			
	Final																																																																																																																																																																										
	Closed In																																																																																																																																																																										
Final Hydrostatic	4271	4253	4275	4287																																																																																																																																																																							
	UTR + Unable to read																																																																																																																																																																										

 Legal Location
 Sec. - Twp. - Rng.

24 - 18S - 25E

 Field Area
 PENASCO

 County
 EDDY

 State
 NEW MEXICO

 Lease Name
 LINCK

 Well No.
 1

 Test No.
 2

 Tested Interval
 8760' - 8880'

 Lease Owner/Company Name
 READING AND BATES, INCORPORATED

— PRESSURE —



— TIME —




43/438-1920

43/438-1919

Each Horizontal Line Equal to 1000 p.s.i.

TICKET NO.	431438	
BT GAUGE NO.	INITIAL	FINAL
1920		
1919		



EXTRAPOLATED PRESSURE GRAPH

Gas Production

B.T. Gauge Numbers			1920	1919	Ticket Number	431438	
Initial Hydrostatic			PRESSURE 4269	PRESSURE 4326	Elevation	3474 ft.	
Final Hydrostatic			4253	4287	1st Flow	- MCF	
1st Flow	Initial	Time	120	471	Production Rate	2nd Flow	110.25 MCF
	Final	29	192	478		3rd Flow	- MCF
	Closed In Pressure	60	3211	3186		Hole Size	7.875 in.
2nd Flow	Initial	Time	150	212	Footage Tested	Net	18 ft.
	Final	121	236	249	Mud Weight	9.2	lbs./gal.
	Closed In Pressure	240	3397	3372	Gas Viscosity	0.023	cp
3rd Flow	Initial	Time			Gas Gravity	Estimated	0.60
	Final				Gas Compressibility	0.90	
	Closed In Pressure				Temperature	154	°F
Extrapolated Static Pressure		1st	-	-			
		2nd	3631	3626			
		3rd	-	-			
Slope P/10		1st	-	-			
		2nd	2514	2400			
		3rd	-	-			

[illegible]

SUMMARY		B.T. Gauge No. 1920 Depth 8741'			B.T. Gauge No. 1919 Depth 8876'			
PRODUCT	EQUATION	FIRST	SECOND	THIRD	FIRST	SECOND	THIRD	UNITS
Transmissability	$\frac{Kh}{\mu} = \frac{1637 Q_r ZT}{m}$		14.53			13.50		md. ft. cp
Theoretical Flow Capacity	$Kh = \frac{Kh}{\mu} \mu$		0.334			0.310		md. ft.
Average Effective Permeability	$K = \frac{Kh}{h}$		-			-		md.
	$K_1 = \frac{Kh}{h_1}$		0.019			0.017		md.
Indicated Flow Capacity	$(Kh)_s = \frac{3200 Q_r \mu ZT \log(0.472 b/r_w)}{P_s^2 - P_r^2}$		0.160			0.156		md. ft.
Damage Ratio	$DR = \frac{\text{Theo. Flow Cap}}{\text{Indicated Flow Cap}} \frac{Kh}{(Kh)_s}$		2.09			1.99		—
Indicated Flow Rate	$OF_1 = \frac{Q_r}{P_s^2 - P_r^2} \quad \text{Max.}$		110.7			110.7		MCFD
	$OF_2 = \frac{Q_r}{\sqrt{P_s^2 - P_r^2}} \quad \text{Min.}$		110.4			110.5		MCFD
Theoretical Potential Rate	$OF_3 = OF_1 DR \quad \text{Max.}$		231.5			220.9		MCFD
	$OF_4 = OF_2 DR \quad \text{Min.}$		231.0			220.4		MCFD
Approx. Radius of Investigation	$b \approx \sqrt{Kt} \text{ or } \sqrt{Kt_0}$		-			-		ft.
	$b_1 \approx \sqrt{K_1 t} \text{ or } \sqrt{K_1 t_0}$		1.99			1.94		ft.
Potentiometric Surface *	$\text{Pot.} = (EI - CD) + (2.319 Ps)$		3153			3006		ft.

NOTICE: These calculations are based upon information furnished by you and taken from Drill Stem Test pressure charts, and are furnished you for your information. In furnishing such calculations and evaluations based thereon, Halliburton is merely expressing its opinion. You agree that Halliburton makes no warranty express or implied as to the accuracy of such calculations or opinions, and that Halliburton shall not be liable for any loss or damage, whether due to negligence or otherwise, in connection with such calculations and opinions.

Casing perms. _____ Bottom choke _____ Surf. temp _____ °F Ticket No. 431438
Gas gravity _____ Oil gravity _____ GOR _____
Spec. gravity _____ Chlorides _____ ppm Res. _____ @ _____ °F

[illegible]



	O. D.	I. D.	LENGTH	DEPTH
Reversing Sub	6 3/4"	2.50"	1'	
Water Cushion Valve				
Drill Pipe	4 3/4"	3.826"	7900'	
Drill Collars	6 3/4"	2.25"	737'	
Handling Sub & Choke Assembly				
Dual CIP Valve				
Dual CIP Sampler				
Hydro-Spring Tester	5"	.75"	4'	8723'
Multiple CIP Sampler	5"	-	4'	
Extension Joint	5"	1"	10'	
AP Running Case	5"	3.87"	5'	8741'
Hydraulic Jar	5"	1.75"	5'	
VR Safety Joint	5"	1"	3'	
Pressure Equalizing Crossover				
Packer Assembly	6 3/4"	1.53"	6'	8754'
Distributor				
Packer Assembly	6 3/4"	1.53"	6'	8760'
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly				
Packer Assembly				
Anchor Pipe Safety Joint				
Side Wall Anchor				
Drill Collars	6 3/4"	2.25"	84'	
Flush Joint Anchor	5 3/4"	3.87"	28'	
Blanked-Off B.T. Running Case	5 3/4"	2.50"	5'	8876'