

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Texas International Petr. Corp.</u>		Lease <u>Vandiver</u>		Well # <u>1</u>	
Location of Well	Unit <u>9905 P</u> <u>5902</u>	Section <u>17</u>	Township <u>18</u>	Range <u>26</u>	County <u>Edley</u>
Drilling Contractor	<u>M L F Rig #10</u>		Type of Equipment <u>Rotary</u>		
<u>V.F. Vesicek</u> APPROVED CASING PROGRAM <u>Verbal approval 11-5-71 1:30 PM.</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 7/8"</u>	<u>48</u>		<u>550</u>	<u>circulate</u>
<u>12 1/2"</u>	<u>8 5/8"</u>	<u>24</u>		<u>1250</u>	<u>"</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>10.5+11.6</u>		<u>9200</u>	<u>300</u>
Casing Data: <u>11 3/4" - 484 - 650 24. 50-50 log 270 gal 2700 cc + 100 net 2700 cc</u>					
Surface <u>42</u> joints of <u>8 5/8"</u> inch <u>24</u> # Grade <u>KS API ST+C Rng</u>					
<u>2</u> New <u>Armed</u> (Approved) (Rejected)					
Inspected by <u>Grossett</u>			date <u>11-8-71</u>		
Cementing Program					
Size of hole <u>11</u>		Size of Casing <u>8 5/8"</u>		Sacks cement required <u>335 CF</u>	
Type of Shoe used <u>Guide</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>Thread Lok</u>					
TD of hole <u>1288</u> Set <u>1285</u> Feet of <u>8 5/8"</u> inch <u>24</u> # Grade <u>above</u>					
New used csg. @ <u>1275 gal</u> with <u>150</u> sacks neat cement around shoe					
+ <u>1</u> sack <u>600</u> additives <u>1/4" Houli</u> (900 CF)					
Plug down @ <u>9:00</u> (AM) (PM) Date <u>11-9-71</u>					
Cement circulated <u>no</u> No. of Sacks					
Cemented by <u>Dowell</u> Witnessed by <u>Grossett</u>					
Temp. Survey ran @ <u>3:00 AM</u> (PM) Date <u>11-8-71</u> top cement @ <u>480</u>					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>LC @ 690 used 3 centralizers 1 in center 2 btm ft.</u>					
<u>1 on 3rd + 5th collars. ran 3/4" to 447 + cemented to surface w/ 150 SX</u>					
<u>in @ 11:30 PM. 11-9-71</u>					

ID 8975 P & A Comp. 2:00 AM. 12-4-71

hole full mud + spot 35 1/4 Class C plugs @ 8900, 87100, 5800, 4450
2275 + 1350 - witnessed by L.M.