

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See rule 1165.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anny _____
 T. Salt _____
 T. Salt _____
 T. Yates _____
 T. 7 Rivers _____
 T. Queen _____
 T. Grayburg _____
 T. San Andres _____
 T. Glorieta 2235
 T. Paddock _____
 T. Blinbry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo 4412
 T. Wolfcamp _____
 T. Penn. _____
 T. Cisco (Bough C) 7053

T. Canyon _____
 T. Strawn _____
 T. Atoka 8560
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Granite _____
 T. Delaware Sand _____
 T. Bone Springs _____
 T. _____
 T. _____
 T. _____

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn. _____
 T. Granite _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1300	2235	938	Dolomite, tan-brown & gray	7705	7990	285	Limestone, brown-tan
2235	2420	182	Sandstone, tan-gray & Dolomite, tan-gray	7990	8560	570	Limestone, brown-tan with some sandstone, white
2420	4412	1992	Dolomite, tan-brown; sandy in part	8560	8746	186	Shale, gray & limestone, gray to brown
4412	5580	1168	Dolomite, tan-brown & white and shale, green and gray	8746	8768	22	Limestone, tan-gray & shale, gray and green
5580	5960	380	Limestone, buff-brown, dolomitic, and shale, gray & green	8768	8802	32	Sandstone, white-gray, oolitic in part
5960	6112	152	Dolomite and limestone, gray-tan, & shale, green	8802	8864	62	Sandstone, white & limestone, oolitic
6112	6320	208	Limestone, cream, gray, tan, and shale, gray	8864	8944	80	Shale, black & sandstone, white
6320	6340	20	Dolomite, gray, argillaceous	8944	8975	31	Shale, dark gray to black
6340	6770	430	Limestone, brown-tan and shale, gray				
6770	7053	283	Shale, gray & brown, limestone, tan brown				
7053	7170	117	Sandstone, white, limy, and shale, gray & brown				
7170	7240	70	Shale, brown and gray, limy				
7240	7705	465	Limestone, tan-brown & white				