

**UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

N. M. D. C. C. COPY
SUBMIT IN TRIPLICATE*
(Other instructor 1 re-verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-025503

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ginsberg Federal

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-18S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

FEB 16 1972

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Hanson Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 1515 - Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1650' FNL & 1800' FEL

Sec. 26, T-18-S, R-30-E, NMPM

Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3450.7 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Surface & Intermediate Csg X
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-07-72 Spudded 17½" hole @ 12:00 PM.

2-08-72 W.O.C. Ran 17 jts. 12-3/4", 34# csg. set @ 720' & cemented w/400 sx. Lite Wate w/3% CaCl & ½# Flocele per sx & 200 sx. Class C w/3% CaCl & ½# Flocele per sx. Plug down @ 5:45 PM. Cement circulated.

2-09-72 Drilling @ 1150', salt & anhydrite. After W.O.C. 12 hours, pressure tested casing to 900# for 30 min. Held O.K.

2-10-72 W.O.C. Drilled to T.D. 1740', anhydrite. Ran 52 jts. 8-5/8", 24# casing & set @ 1740'. Cemented w/50 sx. Class H w/2% CaCl. Plug down @ 10:45 PM on 2-9-72.

RECEIVED
FEB 14 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ronald E. Harrington

TITLE Geologist

DATE 2-10-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
FEB 15 1972
H. L. BEEKMAN
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side