

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY
SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 025503

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ MAR 29 1972

2. NAME OF OPERATOR Hanson Oil Corporation ✓

3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 660' FNL & 1650' FEL
Sec. 26, T-18-S, R-30-E, N.M.P.M.
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3449.0 GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ginsberg Federal

9. WELL NO.

#14

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26, T-18-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Production casing

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3-22-72 Drilled to T.D. 3495' dolomite. Ran logs.

3-23-72 T.D. 3495', dolomite. Cut & pulled 1530' of 8-5/8" casing. Ran 114 joints, 5-1/2", 15.5# casing set at 3495'. Cemented with 950 sx. LiteWate with 1/4# Flocele per sx. + 150 sx. Class "C" with 5# sand and 8# CaCl per sx. Cement circulated. Plug down @ 9:00 PM on 3-23-72.

18. I hereby certify that the foregoing is true and correct

SIGNED

Gerald E. Harrington

TITLE

Geologist

DATE

MAR 27, 1972

(This space for Federal or State office use)

APPROVED BY
CONDITION OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
MAR 28 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICOAPPROVED
MAR 23 1972
H. L. BECKMAN
ACTING DISTRICT ENGINEER