

N. M. RECEIVED
SUBMIT IN DUPLICATEForm approved
Budget Bureau No. 42-R355.5.UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(See other instructions on reverse side)

MAY 17 1972

5. LEASE DESIGNATION AND SERIAL NO.

NM 025503

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ginsberg Federal

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 26, T-18-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ARTESIA, OFFICE

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR

Hanson Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Box 1515-Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

660' FNL & 1650' FEL

At top prod. interval reported below

Sec 26, T-18-S, R-30-E, N.M.P.M.

At total depth

Eddy County, New Mexico

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

3-15-72

16. DATE T.D. REACHED

3-22-72

17. DATE COMPL. (Ready to prod.)

4-5-72

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3449' GL

19. ELEV. CASINGHEAD

3449'

20. TOTAL DEPTH, MD & TVD

3495'

21. PLUG, BACK T.D., MD & TVD

3495'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-3495'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

3109 - 3113' Penrose

3376 - 3382' Grayburg

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Densilog, Induction-Electrolog

MAY 16 1972

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	AMOUNT PULLED
12-3/4"	34#	716'	17-1/2"	600 sx. - circulated
5-1/2"	15.5#	3495'	7-7/8"	1100 sx. - circulated

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	3405'	3182'

31. PERFORATION RECORD (Interval, size and number)

3109 - 3113', 0.41", 12 holes

3314 - 3318', 0.41", 12 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3314 - 3318'	20,000 gal. gelled wtr. + 20,000# 20-40 sand + 500 gals acid
3109 - 3113'	20,000 gal. gelled wtr. + 20,000# 20-40 sand + 500 gals acid

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
4-5-72		Flowing				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
4-5-72	24	18/64"	→	25			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
200#	900#	→	25			38 ⁰	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented-pending connection by Phillips Petroleum

TEST WITNESSED BY

Bill Morgan

35. LIST OF ATTACHMENTS

Deviation Survey, 2 copies-logs

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Gerald E. Harrington

TITLE

Geologist

DATE

May 15, 1972

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Anhydrite	467'	
				Salt	645'	
				B of Salt	1574'	
				Yates	1804'	
				Queen	2823'	
				Grayburg	3247'	