

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION
3 - NMOCC - Artesia
1 - File
AUG 17 1972

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1565
7. Unit Agreement Name
8. Farm or Lease Name State BJ
9. Well No. 2
10. Field and Pool, or Wildcat Shugart
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Getty Oil Company
3. Address of Operator Box 249, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER C, 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 18S RANGE 30E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3524 Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Leatherwood Drilling spudded at 8:45 AM 8-6-72. Drilled 11" hole to 784'. Set 8-5/8" 24# J-55 casing @ 780'. Cemented with 325 sacks Class "C" with 1/4#/sx. flocele and 2% Cacl. Circulated estimated 5 sacks cement. W.O.C. 18 hours. Tested 8-5/8" casing with 1,000# for 30 minutes, no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By

SIGNED C. L. WADE TITLE Area Supt. DATE 8-16-72

APPROVED BY W. A. Gussert TITLE OIL AND GAS INSPECTOR DATE AUG 18 1972

CONDITIONS OF APPROVAL, IF ANY: