

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 11323	
2. NAME OF OPERATOR Coquina Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 200 Bldg. of Southwest, Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 660' FEL		8. FARM OR LEASE NAME Five Mile Unit	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 3470' KB 3480'		10. FIELD AND POOL, OR WILDCAT Atoka, Morrow, West (Gas)	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14, T18S, R25E	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☒REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

Setting &amp; Cementing Casing.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

One December 1, 1972, drilled 24" hole to 35' with rat hole machine. Cemented 20" conductor casing at 35' with 4 1/2 cu. yards of Redi-Mix cement.

MIRT. Spudded - drilled 17 1/2" hole to 510'. Cemented 13 3/8" 48#H40 ST&C 8rd new API casing at 500.87' with 400 sacks Howco Lite Wate cement, followed by 100 sacks Class C 2% Calcium Chloride. Circulated 50 sacks cement. Plud down 8:45 AM, December 8, 1972. WOC 13 1/4" hours. Tested 13 3/8" to 400 psi. Drilled out with 11" bit.

RECEIVED  
DEC 12 1972  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

SIGNED

(Ben D. Gould)

TITLE

Engineer

DATE

12-11-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side