

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 1 1973

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Pennzoil Company	8. Farm or Lease Name Vandiver
3. Address of Operator P. O. Drawer 1828 - Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>18-S</u> RANGE <u>25-E</u> NMPM.	10. Field and Pool, or Wildcat West Atoka Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3440' G.L.	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐ CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-28-73 Drill 12 1/4" hole below 13 3/8" casing.

5-30-73 T.D. 1,325'. Ran 41 jts. 8 5/8", 24#, J-55, casing & set @ 1325'. Cement w/275 sx Class "C" w/4% gel & 150 sx Class "C" with 1/4# flocele w/2%CaCl. Cement did not circulate. W.O.C. 8 hrs. Ran temperature survey. Top of cement @ 900'.

5-31-73 Ran 1" down outside 8 5/8" to 900'. Cement w/75 sx Class "C" with 1/4# flocele & 2% CaCl. Did not circulate. W.O.C. 4 hrs. Re-cement down 1" tbq. w/445 sx Class "C" w/2% CaCl + 1/2# flocele. Did not circulate. W.O.C. 4 hrs.

6-1-73 Re-cement down 1" tbq. w/45 sx with 3% CaCl. W.O.C. 4 hrs. Top of cement @ 202' (130' inside 13 3/8" casing).

6-2-73 W.O.C. 18 hrs. Tested 8 5/8" csg. to 1500 psi for 30 min. O.K. - Drilling 7 7/8" hole.

Note: Total of 990 sx cement behind 8 5/8" casing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. C. Raney TITLE Petroleum Engineer DATE 6-11-73

APPROVED BY W. P. Gressett TITLE OIL AND GAS INSPECTOR DATE JUN 19 1973

CONDITIONS OF APPROVAL, IF ANY: