

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon <u>6994</u>	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>7779 7719</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>8328</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss <u>8839</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>900</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>2283</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>4282</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. <u>Monterey 8623</u>	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECCRD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	350	350	Surface	7475	7557	82	Line and sand
350	505	155	Red bed	7557	7643	86	Lime
505	860	355	Red bed and sand	7643	8451	808	Lime and shale
860	1318	458	Anhydrite and sand	8451	8627	176	Lime, shale and sand
1318	2410	1092	Lime	8627	8865	238	Lime and shale
2410	3040	630	Lime and anhydrite				
3040	3460	420	Lime				
3460	3595	135	Lime & Shale				
3595	4376	781	Lime				
4376	4582	206	Lime and sand				
4582	4642	60	Lime, sand and shale				
4642	5422	780	Lime				
5422	5527	105	Lime and shale				
5527	6104	577	Lime				
6104	7339	1235	Lime and shale				
7339	7475	136	Lime, shale and sand				