

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUN 29 1978

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		3. E. C. C. ARTESIA, OFFICE		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		7. Unit Agreement Name		5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, NM, 88210		8. Farm or Lease Name Armstrong "CT" Com		
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 5 TOWNSHIP 18S RANGE 26E NMPM.		9. Well No. 1		
15. Elevation (Show whether DF, RT, GR, etc.) 3397' KB		10. Field and Pool, or Wildcat Eagle Creek Strawn		
		12. County Eddy		

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER Perf and Treat Strawn zone <input checked="" type="checkbox"/>	
		TA Eagle Creek Atoka-Morrow	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

6-20-78

Set a standing valve in the Atoka packer at 8314' and retrievable bridge plug at 8312'. Perforated 8122-26' (8 shots), 8050-56' (12 shots) (Total 20.34" shots). (Strawn formation) - Treated perforations w/1500 gallons 15% DS-30 acid. Flowed back load and well cleaned up and flowed 130# on 1/2" choke = 800 MCFPD

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 6-28-78

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 30 1978