

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved,  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 59954

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Loco Hills #4 S. Ut.

8. FARM OR LEASE NAME

Tract 12

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Loco Hills O. G. B. S. A.

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 9-18S-29E. NMPM

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

NEWMONT OIL COMPANY

AUG 15 1973

3. ADDRESS OF OPERATOR

P.O. Box 1305, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

330' FSL &amp; 330' FEL Section 9, T-18S, R-29E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3494 Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Production String.

XX

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

7/17/73- Drilled 7 7/8" hole from 330' to 2575'. Conditioned hole and ran Dual Laterolog and Gamma Ray Density log.

7/18/73- Ran drill pipe back in and circulated hole, pulled drill pipe and laid down. Ran guide shoe on bottom of 11' joint and self fill-up float valve on top. Ran a total of 2575' of 4 1/2", 9.5#, K-55 pipe with centralizers on bottom 5 collars. Cemented with 450 sacks light cement made up of 60 % Class "C" with 40% Pozmix and 6% Gel. 2% CaCl<sub>2</sub> (Slurry Wt. 12.7#/gal) followed with 100 sacks Class "H" with 3/4% friction reducer, 5# salt and 10# No. 3 sand per sack (Slurry Wt. 16.2#/gal) Shut in waiting on cement. Cement top at 800' by Kuster K-3 bomb.

7/20/73 Perforated w/2 shots per foot from 2522' to 2534' GLM.

RECEIVED

AUG 14 1973

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Charles E. Joy*

TITLE District Superintendent

DATE

8/14/73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 14 1973  
K. L. BEEKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side