

N. M. O. C. G. COBY

SUBMIT IN T ICATE*

(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1425.UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☐GAS
WELL ☒

OTHER

SINGLE
ZONE ☐MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

Coquina Oil Corporation

3. ADDRESS OF OPERATOR

200 Bldg. of the Southwest, Midland, Tx. 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1980' FNL & 1980' FEL

At proposed prod. zone

Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

4 Miles Southwest of Artesia

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.

(Also to nearest drlg. unit line, if any)

660'

18. DISTANCE FROM PROPOSED LOCATION*

TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

--

16. NO. OF ACRES IN LEASE

320

19. PROPOSED DEPTH

8,800

17. NO. OF ACRES ASSIGNED
TO THIS WELL

320

20. ROTARY OR CABLE TOOLS

Rotary & Cable Tools

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3437 GL

22. APPROX. DATE WORK WILL START*

June 25, 1973

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17 1/4	13 3/8	48	500	Circulate
12 1/4	8 5/8	24	1300	Circulate
7 7/8	4 1/2	10.5, 11.6	8800	To Be Determined

Spud with cable tools and drill 15" hole into San Andres at 500 Ft. Run 13 3/8" casing and cement back to surface. Move off cable tools and rig up rotary. Drill 12 1/4" hole to approximately 1300'. Cement 8 5/8" casing at 1300' and circulate cement above 500'. Drill 7 7/8" hole to T.D. Blow out Preventers. Will be installed on 8 5/8" casing after it has been cemented and will be kept installed until T.D. B.O.P. diagram attached.

RECEIVED
JUN-6 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

(Ben Gould)

TITLE

Superintendent

DATE

6-5-73

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

APPROVED
JUN 14 1973
R. L. BEEKMAN
ACTING DISTRICT ENGINEERTHIS APPROVAL IS RESCINDED IF
OPERATIONS
ARE NOT COMMENCED WITHIN 3 MONTHS.
SEP 14 1973
*See Instructions On Reverse SideDECLARED WATER BASIN
13 3/8"CEMENT BEHIND THE
CASING MUST BE CIRCULATED
8 5/8"NOTIFY USGS IN SUFFICIENT TIME TO
INSPECT THE CASING.