

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Mark Production Co.</i>		Lease <i>Peterson "Com"</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980s+e</i>	Section <i>7</i>	Township <i>18</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary to start approx 8-1-73</i>		

* Cement behind 8 3/8" must come up inside
11 3/4" + verified by temp. survey

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
20"	16"	65		200	250 lbs.
15"	11 3/4"	42		900	875 "
11"	8 3/8"	24		1850	350
7 7/8"	4 1/2"	10.5 + 11.6		9700	330

Casing Data:

Surface *24* joints of *11 3/4* inch *42* # Grade *New API K-55*
ATC (Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole *15" TD* Size of Casing *11 3/4* Sacks cement required *540*

Type of Shoe used *Build* Float collar used *Insert* Btm 3 jts welded *Thread Lock*

TD of hole *915'* Set *900'* Feet of *11 3/4* Inch *42* # Grade *K-55*

New-used csg. @ *900'* with *100* sacks neat cement around shoe *Class 2% cc 15.6*

+ *440* sax *Hawco lite*, additives *3# Gilsonite 1/4# Flocc 2% cc 12.7*

Plug down @ *2:00* (AM) (PM) Date *8-22-73*

Cement circulated _____ No. of Sacks *75/sx*

Cemented by _____ Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____