

N. M. G. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN THE (CATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0516714

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Hondo Drilling Company

3. ADDRESS OF OPERATOR

P. O. Box 116, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface660' EN & 545' FWL, Section 31, T-18-S, R-27-E, N.M.P.M.,
Fddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3280' GR

7. UNIT AGREEMENT NAME

Kaiser Lake Unit

8. FARM OR LEASE NAME

Kaiser Lake Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

floodat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T-18-S, R-27-E, N.M.P.M.

12. COUNTY OR PARISH

Fddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Drilling Report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

8-30-73 Spud 17 1/2" surface hole at 1:00 P.M., drilled to 335 ft.

8-31-73 Ran 11 joints 13-3/8" casing H-40 48 lb. ST&C casing, total of
339 ft., set at 335 ft., cemented with 365 sacks Class "C" cement,
circulated cement and plug down at 9:30 A.M.

9-1-73 Drilling 11" surface hole at 1121 ft. total depth.

9-2-73 Ran 36 joints 8-5/8" casing, 24 lb. K-55 ST&C casing, total of 1130 ft.,
set at 1120 ft. Cemented with 500 sacks Class "C" cement with 2%
C.C., cement circulated. Plug down at 3:30 A.M.9-3-73 pressure test Blow out Preventers & 8-5/8" casing with 1,000# pressure.
Drilling 7-7/8" hole at 1235 ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE Sept. 4, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

SEP 5 1973

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.