12 1/4"

9-5/8"

7." or

## N. M. O. C. C. COMPLETE

(Other instructions on reverse side)

Form approved. Budget Burean No. 42 R1425.

## UNITED STATES DEPARTMENT OF THE INTERIOR

4	ڐ	<u> </u>	0/5-	_	0	96	7
į	5.	LEASE	DESIGNA	TION	AND	BEETA	NO.

	GEOLO	GICAL SURVE	ΞY			<i>/</i> //	W 042	10087		
APPLICATION	Y FOR PERMIT	O DRILL, D	EEPE	N, OR I	LUG B	ACK	G. IF 18	DIAN, ALLC	TTEE (	OR THIBE NAME
1a. TYPE OF WORK DRI	ILL. 🟋	DEEPEN [	]	PL	UG BAC	:к 🗆	7, UNIT	AGREEMEI	NT NAI	4E
b. TYPE OF WELL OIL C. WELL C. WELL C. W 2. NAME OF OPERATOR	AS XX OTHER		81 <b>Z</b> 0	NGLE XXR	Em tirtin	E [ ] <b>[</b>		on LEASE		
Yates Petr	coleum Corpor	ation /		···· - · · · · · · · · · · · · · · · ·	SEP 2	6 1973	9. WEL	1, NO.		
	4th Street -					-		D AND POO		
4. LOCATION OF WELL (R At surface	eport location clearly and	in accordance with	any S	tate requirem	ents.*)	arr les. me ^am	/ W:	ildcat		
1980	)' FNL and 66	0' FEL of	Sec	7-18	S-25 P	2 Beilie Bank	11. SEC	., T., R., M., SURVEY O	OR BL	K.
At proposed prod. zon			R	ECE	V 1	Í	Sec. Unit	7-189 H Ni		δE
14. DISTANCE IN MILES	and direction from NEA				1011-1			NTY OR PAI	IISH	13. STATE
7 miles w	est of Atoka			JE,	SAL SUK	AE,	Eddy	<i>!</i>		NM
15. DISTANCE FROM PROPORTION TO NEAREST PROPERTY OR LEASE I (Also to nearest drip	r Jine, ft.		16 <b>J</b> .N	SEP-6 1.06501.00 RTESIA, N	MAN MEXI	TO TH	F ACRES	320		
18. DISTANCE FROM PROP TO NEAREST WELL, D OR APPLIED FOR, ON TH	RILLING, COMPLETED,		19. PR	orosed depth orox. 8	Į.	20. ROTAR	tary	BLE TOOLS		
21. ELEVATIONS (Show who	ether DF, RT, GR, etc.)						1			WILL START*
	3615	GR					As	soon	as	approved
23.	· I	PROPOSED CASIN	G AND	CEMENTIN	G PROGRA	М				
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FO	от	SETTING				NTITY OF C	EMENT	
71/11	1 2 2 /Q!	101-		Annray	200	Circ	+ c f 112	- 04		

Propose to drill and test the Morrow sand and intermediate formations. Approx 200' 13-3/8" will be cemented for protection from surface gravel and 9-5/8" casing will be run and cemented 100' below the Artesian Zone.

Approx 1000'

Approx 8500'

Mud Program: - Fresh water gel to 1000', water to 6500', flosal and drispak to TD.

23# & 26#

15.5# & 17#

BOP Program: - BOP's will be installed on Intermediate. Hydril will be installed and tested prior to drilling the Wolfcamp; pipe rams will be tested daily, blind rams on trips.

	proposal is to deepen or plug back, give data on present lly, give pertinent data on subsurface locations and me	
SIGNED Eddin Middy	Engineer Engineer	9-5-73
(2) the space of File al or State office use)	Subject to fisc. 5. My	sprading the nel
CTING DISTRICT ENGINEERAL, IF INY:	SUBJECT TO ATTACHED DEEP WELL CONTROL	DECTARED WATER BASIN
THIS APPROVA' IS RECOINDED IF OPERATIONS ARE NOT COMMENCED WITHIN 3 MONTHS.	*See Instructions On Reverse Side	CEMENT BEHIND THE 235 CASING MUST BE CIRCULATED
ARE NOT COMME	MATIEV III	CS 10 SE TENDEDT TIMETO

--- DEC 25 1973

NOTIFY USGS IN SUFFICIENT TIME TO, 175

Ciruclated

250 sx or as expedient