

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

MAR 13 1974

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS, ARTESIA, OFFICE  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Water Injection</b>		7. Unit Agreement Name <b>Ballard Grayburg San Andres Unit</b>
2. Name of Operator <b>Anadarko Production Company</b>		8. Farm or Lease Name <b>Tract No. 25</b>
3. Address of Operator <b>P. O. Box 67, Loco Hills, New Mexico 88255</b>		9. Well No. <b>4</b>
4. Location of Well UNIT LETTER <b>J</b> , <b>1980</b> FEET FROM THE <b>South</b> LINE AND <b>1780</b> FEET FROM THE <b>East</b> LINE, SECTION <b>5</b> TOWNSHIP <b>18S</b> RANGE <b>29E</b> NMPM.		10. Field and Pool, or Wildcat <b>Loco Hills Grayburg San Andres</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3545.7' GR</b>		12. County <b>Eddy</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER **Spud & Set Casing** ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 $\frac{1}{4}$ " hole on 3-1-74. Drilled to 363' KB, set 8 5/8" Casing @ 359' KB, cemented with 150 sacks. Let cement set 18 hours and tested to 500 PSI--O. K.

Drilled to TD 2800 KB, ran Logs, set 4 $\frac{1}{2}$ " casing @ 2800 KB, cemented with 250 sacks class H cement. Intend to perforate Grayburg Sand Zones and equip with tubing and packer for completion as water injection well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed by  
SIGNED **Jerry E. Buckles** TITLE **Area Supervisor** DATE **12 March 1974**

APPROVED BY **W. R. Greer** TITLE **OIL AND GAS INSPECTOR** DATE **MAR 13 1974**  
CONDITIONS OF APPROVAL, IF ANY: