

COPIES RECEIVED	5
CONTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 17 1974

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS O. C. C.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT AREA. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- RE-Entry	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Gushwa "DR"
3. Address of Operator 207 South 4th Street-Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER E, 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 35 TOWNSHIP 18S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Penasco Draw (Yeso SA)
5. Elevation (Show whether DF, RT, GR, etc.) 3509' KB	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒ Re-entry, sq, perf Wolfcamp & treat, sq Wolfcamp. Cmt, Perf & Sand Frac for Yeso Completion.

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 9220'. Pulled 2-7/8" tubing & packer, set bridge plug at 8700' perforated w/2 holes at 5950' and squeezed w/275 sx. Perforated the Wolfcamp at 5734-5756'. Treated perfs w/1000 gallons of 15% DS-30 acid. Swabbed back 100% water. Non-commercial. Sq Wolfcamp perforations w/75 sx. Perforated w/2 shots at 3000' and cemented casing w/600 sx (Top of cement estimated at 650') PBT 2886' - Perforated Yeso as follows w/35 .42" jet shots. 2354-63 4/shots; 2324-28 3/shots; 2297-99 2/shots; 2262-70 5/shots; 2337-51 10/shots; 2222-26 3/shots; 2188-2207 8/shots. Sand Frac'd w/1000 gallons of BDA, 80000# 20-40 sand and 80000 gallons of treated water. Hung on beam and put well on production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. J. [Signature] TITLE Engineer DATE 9-17-74

APPROVED BY W. A. [Signature] TITLE OIL AND GAS INSPECTOR DATE SEP 18 1974

CONDITIONS OF APPROVAL, IF ANY: