

N. M. O. G. S. OFFICE
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instruction
verse side)DATE
on re-Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-067136

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 34, T-18-S, R-25-E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Belco Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

2000 Wilco Building, Midland, Texas 79701 ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FEL of Section 34

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3506' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Setting casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded on 12/8/73. Drilled 17-1/2" hole to 320'. Ran 8 jts. of 12-3/4" casing, 32# surface casing at 320'. Cemented casing with 350 sx. Class "C" with 2% CaCl. Circulated 35 sx. to surface. Plug down at 5:30 A.M.

Drilled 11" hole to 1115'. Ran 35 jts. of 8-5/8", 24# K-55 CF&I casing set at 1111'. Cemented with 400 sx. of Howco Lite with 10# gilsonite, 1/4# flocele and 2% CaCl, followed with 150 sx. of Class "C" with 2% CaCl. Plug down at 12:30 P.M. Circulated out 35 sx. of cement to surface. W.O.C. 18 hours. Tested casing to 800# for 30 mins. Held okay.

RECEIVED

JAN 11 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Glenn Cope
Glenn Cope

TITLE

District Engineer

DATE

1/10/74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side