

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP DATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 064488

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Penasco Draw (S. J. Yeso)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 26-18S-25E
Unit II IMPH

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

DEC 16 1974

O. C. C.

ARTESIA OFFICE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

2310' FNL & 150' FEL of Sec. 26-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3563' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) Set prod. csg. ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 2552'; PBTD 2460'. Ran 56 jts of 4½" 9.5#, J-55 used casing (1814.44'), 16 joints of 4½" 10.5#, J-55 new casing (645.31') (Total 2459.75'), 1-4½" Davis shoe, centralizers at 2400, 2350, 2260, 2215, 2170, 1450, 1430, 1410, 1390, 1370, 1350'. Cemented at 2460' w/250 sacks Class C cement. PD 6:30 PM 11-20-74. WOC 18 hours and tested casing to 1000#. OK. Perforated w/38 .42" jet shots as follows: 2124, 2128, 2133½, 2141½, 2145, 2149, 2155½, 2165, 2168, 2173, 2177, 2232, 2239, 2245, 2251, 2283, 2119½, 2122, 2126, 2132, 2143, 2147, 2151½, 2153, 2157, 2159, 2166½, 2170, 2171½, 2175, 2230½, 2235, 2241½, 2243, 2247, 2248½, 2281½, 2284½. Sand Frac'd using 3000 gallons 15% acid for breakdown, 200000# 20-40 sand and 100000 gallons of treated water.

RECEIVED
DEC 12 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddie M. Halyard

TITLE

Engineer

DATE

12-9-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
DEC 13 1974
R. L. BEEKMANN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side