

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

ELL API NO.

30-015-21079

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

☐

GAS

WELL ☒

OTHER

2. Name of Operator

Unit Petroleum Company

3. Address of Operator

P.O. Box 702500, Tulsa, OK 74170-2500

7. Lease Name or Unit Agreement Name

Hare

8. Well No.

1

9. Pool name or Wildcat

Atoka (Morrow) W. Gas

4. Well Location

Unit Letter P : 660 Feet From The south Line and 660 Feet From The east Line

Section 12

Township 18S

Range 25E

NMPM Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3449-KB Datum

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE/DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Release pkr at 8,570'. Circ hole w/plug mud. Pull out of hole w/tbg.
- 2) Set 4 1/2" CIBP at 8,550'. Dump bail 35' cement on top
- 3) Find freepoint of 4 1/2" csg and shoot off as deep as possible. (TOC at 6,640'). POOH w/csg
- 4) Spot 100' cement plugs as follows: 2548-6572
 - A) across 4 1/2" csg stub (50' above and below) TAG.
 - B) across ABO top at 4,255'
 - C) across Glorietta top at 2,188'
 - D) across 9" csg shoe at 1,200' (50' above and below.) This plug will be tagged w/wireline or tbg
- 5) Circ cement to surface from 362' (50' below 12-3/4" shoe)
- 6) Cut off & wled on ID plate

NOTE: Work to begin upon approval.

Get between all plugs.

Please notify NMCC 24 hrs in advance of P & A

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Brent A. Keys

TITLE

Production Engineer

DATE

12/9/97

TYPE OR PRINT NAME

Brent A. Keys

TELEPHONE NO.

(918) 493-7700

(This space for State Use)

APPROVED BY TIM W. GALE

CHIEF OF DIVISION

APPROVED BY

TITLE

DATE

JAN 20 1998

CONDITIONS OF APPROVAL, IF ANY: