

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TWO COPIES
(Other Instructions on Reverse Side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

458

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <i>PxA</i>	7. UNIT AGREEMENT NAME <i>Com-SW-959</i>
2. NAME OF OPERATOR <i>AMOCO PRODUCTION COMPANY</i>	8. FARM OR LEASE NAME <i>Hondo B Federal Gas Com</i>
3. ADDRESS OF OPERATOR <i>P.O. BOX 68 HOBBS, NEW MEXICO 88240</i>	9. WELL NO. <i>1</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>2310' F2L x 660' FWL (UNIT L, NW1/4, SW1/4)</i>	10. FIELD AND POOL, OR WILDCAT <i>Red Lake - Penn</i>
14. PERMIT NO. <i>3001521114</i>	15. ELEVATIONS (Show whether on RT, GR, etc.) <i>3405' RAB</i> <i>O. C. D. ARTESIA, OFFICE</i>
12. COUNTY OR PARISH <i>Eddy</i>	13. STATE <i>NM</i>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. MISU and POH with packer and tubing.
2. Ran CIBP and set at 8720'. Capped with 105X class H cement and displaced w/brine gel.
3. Pulled up to 8075' and pumped 205X class H cement. Displaced w/brine gel.
4. Pulled up to 6218' and pumped 205X class C cement. Displaced w/brine gel.
5. Pulled up to 5175' and pumped 205X class C cement. Displaced w/brine gel.
6. Pulled up to 3145' and pumped 205X class C cement. Displaced w/brine gel.
7. Found hole in casing at 2885-90'. Set cement retainer at 1950'. Spaced out 1550' class C cement and circulated 305X out 8 7/8" casing.
8. Pulled up to 120' and pumped 155X class C cement surface plug.
9. Installed dry hole Marker and MOSU 12/4/85.

0 + 5 BLM C, 1 - JRB, 1 - FJN, 1 - CMH

18. I hereby certify that the foregoing is true and correct

SIGNED *Charles M. Herring* TITLE *Administrative Analyst (SG)* DATE *12/5/85*

(This space for Federal or State office use)

APPROVED BY *UR Bredberg* TITLE *Asst. Dir.* DATE *6.29.87*

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side