

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>David Fasken</i>		Lease <i>Rogers 10 com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>16505 6600</i>	Section <i>10</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor	<i>Walter Dryden</i>		Type of Equipment <i>Rotary to start approx 5-1-74</i>		
APPROVED CASING PROGRAM <i>4-22-74</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>34"</i>	<i>20"</i>	<i>96.40</i>		<i>35'</i>	<i>Ready mix</i>
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>1200</i>	<i>1250 cwt.</i>
<i>12"</i>	<i>8 3/8"</i>	<i>28</i>		<i>1800</i>	<i>250</i>
<i>7 7/8"</i>	<i>4 1/2"</i>			<i>9200</i>	
Casing Data:					
Surface <i>36</i> joints of <i>12 3/8</i> inch <i>48</i> # Grade <i>API New 48" H-40</i>					
(Approved) (Rejected)					
Inspected by <i>S. J. ...</i> date <i>5-16-74</i>					
Cementing Program					
Size of hole <i>17 1/2</i> Size of Casing <i>13 3/8</i> Sacks cement required					
Type of Shoe used <i>Texas</i> Float collar used <i>Insert Btm</i> # jts welded <i>Btm It.</i>					
TD of hole <i>121240</i> Set <i>11986</i> Feet of <i>13 3/8</i> Inch <i>48</i> # Grade <i>H-40</i>					
New-used csg @ <i>1100</i> with <i>250</i> sacks near cement around shoe <i>14,110</i>					