

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP. TE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-B1434.

5. LEASE DESIGNATION AND SERIAL NO.

NM 021096

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR FRANKLIN, ASTON & FAIR, INC. ✓		8. FARM OR LEASE NAME Yates Federal ✓	
3. ADDRESS OF OPERATOR P. O. Box 1090, Roswell, New Mexico 88201		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 660' FSL, Section 12-18S-30E		10. FIELD AND POOL, OR WILDCAT Shugart	
14. PERMIT NO.		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 12, T18S, R30E, N.M.P.M.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3537 GR		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was spudded June 6, 1974; 8-5/8" casing was set at 539 feet with 300 sacks of Class C cement circulated to surface. The well was drilled to 3830' in the top of the San Andres. ~~Proposed to plug and abandon as follows:~~

50 sack cement plug 3600-3450' across Loco Hills sand
35 sack cement plug 1650-1550' at base of the salt
35 sack cement plug in and out of base of 8-5/8" casing at 600-500'
20 sack plug and marker at surface.

Structural position and logs indicate the well to be a dry hole.

RECEIVED

JUN 28 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Krant N SmithTITLE GeologistDATE June 21, 1974

(This space for Federal or State office use)

APPROVED BY DEC 3 1974
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side