

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 021096

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, INC. ✓

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FEL & 660' FSL, Section 12-18S-30E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates Federal '81'

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., E., M., OR BLE. AND
SURVEY OR AREA

Sec. 12, T18S, R30E, N.M.P.M

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3537 GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was spudded June 6, 1974; 8-5/8" casing was set at 539 feet with 300 sacks of Class C cement circulated to surface. The well was drilled to 3830' in the top of the San Andres. On June 18, 1974, pursuant to telephone conversation with Mr. Knauf, the well was plugged and abandoned as follows:

50 sack cement plug 3600-3450' across Loco Hills sand
35 sack cement plug 1650-1550' at base of the salt
35 sack cement plug in and out of base of 8-5/8" casing at 600-500'
20 sack plug and marker at surface.

Structural position and logs indicate the well to be a dry hole.

RECEIVED

NOV 12 1975

O. C. C.
ARTESIA, OFFICE

RECEIVED

JUN 28 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Grant N. SmithTITLE GeologistDATE June 21, 1974

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

printed
ID-2
3-1-75