

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other Instructions
verse side)

FE-
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 01159

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FAF - Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Devonian Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 4-T18S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy County New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Franklin, Aston & Fair, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 1090 Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1980' FSL & 660' FWL

Section 4-18S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3555' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Plug back for completion

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On November 8, 1974, this well was plugged back from 12,600' TD in the Devonian to the base of 9-5/8" casing set at 3650' in the San Andres formation. The cement plugs are as follows:

100' cement plug	12,600'-12,500'	Devonian
100' cement plug	10,450'-10,350'	Pennsylvanian (Strawn)
100' cement plug	9,400'-9,300'	Wolfcamp
100' cement plug	6,700'-6,600'	Bonesprings
100' cement plug	3,700'-3,600'	Base of 9-5/8 @ 3650'.

On December 12, 1974, the San Andres formation was perforated 1 jet shot per foot; 3546' - 3556' and acidized with 1500 gal of acid.

RECEIVED

JUL 1 1975

O. C. C.
ARTEBIA, OFFICE

RECEIVED

JUN 18 1975

U. S. GEOLOGICAL SURVEY
ARTEBIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geologist

DATE

6-25-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

JUN 26 1975

CONDITIONS OF APPROVAL, IF ANY: