

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instruction,
verse side)

Form approved.
Budget Bureau No. 42-R1424.

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. NM 01159
2. NAME OF OPERATOR Franklin, Aston & Fair, Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 1090 Roswell, New Mexico 88201	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 660' FWL Section 4-18S-30E	8. FARM OR LEASE NAME FAF - Federal
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3555' GR	10. FIELD AND POOL, OR WILDCAT Devonian Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 4-T18S-R30E
	12. COUNTY OR PARISH Eddy County
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Plug back for completion

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

On November 8, 1974, this well was plugged back from 12,600' TD in the Devonian to the base of 9-5/8" casing set at 3650' in the San Andres formation. The cement plugs are as follows:

100' cement plug	12,600'-12,500'	Devonian
100' cement plug	10,450'-10,350'	Pennsylvanian (Strawn)
100' cement plug	9,400'- 9,300'	Wolfcamp
100' cement plug	6,700'-6,600'	Bonesprings
100' cement plug	3,700'- 3,600'	Base of 9-5/8 @ 3650'.

On December 12, 1974, the San Andres formation was perforated 1 jet shot per foot; 3546' - 3556' and acidized with 1500 gal of acid.

RECEIVED
JUN 11 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geologist

DATE

6-25-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DISTRICT ENGINEER

DATE

JUN 26 1975

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side