

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Texas Pacific Oil Co. 3rd. H.E. Kissinger Comm #1</u>		Lease		Well # <u>#1</u>	
Location of Well	Unit <u>F</u>	Section <u>10</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>1650 FN 1650 FN</u> <u>Warton Dels G.</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>26"</u>	<u>20"</u>	<u>94 #</u>		<u>200'</u>	<u>Circ</u>
<u>17 1/2"</u>	<u>13 3/4"</u>	<u>48 #</u>		<u>1200'</u>	<u>Circ</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24 #</u>		<u>1500'</u>	<u>Circ</u>

Casing Data:

Surface 35 joints of 12 1/2 inch 48 # Grade 10
(Approved) (Rejected)

Inspected by W. Smith date 10-20-74

Cementing Program

Size of hole 17 1/2 Size of Casing 12 1/2 Sacks cement required 25

Type of Shoe used fixed Float collar used yes Btm 3 jts welded yes

TD of hole 1650 Set 22 Feet of 12 Inch 48 # Grade 10

New-~~used~~ csg. @ 200' with 500 sacks neat cement around shoe
+ 1 sax Super additives

Plug down @ 200' (AM) (PM) Date 10-20-74

Cement circulated 25 No. of Sacks 25

Cemented by W. Smith Witnessed by W. Smith

Temp. Survey ran @ 10 (AM) (PM) Date 10-20-74 top cement @ 200'

Casing test @ 200' (AM) (PM) Date 10-20-74

Method Used W. Smith Witnessed by W. Smith

Checked for shut off @ 200' (AM) (PM) Date 10-20-74

Method used W. Smith Witnessed by W. Smith

Remarks: 200' - 1650' - 1650' - 1650'

1650' - 1650' - 1650' - 1650'

1650' - 1650' - 1650' - 1650'

1650' - 1650' - 1650' - 1650'