

CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 1-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fed. ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER RESERVOIR" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- DRY	7. Unit Agreement Name
2. Name of Operator RALPH NIX	8. Farm or Lease Name IRENE
3. Address of Operator P. O. Box 617, Artesia, New Mexico 88210	9. Well No. #1
4. Location of Well UNIT LETTER <u>E</u> <u>1650'</u> FEET FROM THE <u>North</u> LINE AND <u>1650'</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> N.M.P.M.	10. Field and Pool, or Wildcat Atoka San Andres
11. Elevation (Show whether DF, RT, CR, etc.) 3338' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	
OTHER ☐			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/25/81 Circulate hole with gelled water.
1st plug pumped 50 sx. Class H. cement, with 2% CLCH from 1580'-1480'
WOC 2 hrs. unable to tag plug. 2nd plug pumped 75 sx. Class H. cement
with 2% CLCH from 1580' to 1480' WOC 2 hrs. unable to tag plug.
3rd. plug pumped 75 sx. Class H. cement with 2% CLCH from 1580' to 1480'
WOC 17 hrs.
2 3/8" tubing cemented in hole, top of cement at 1090'.
OCC Rep. Approved for surface plug to be set after tubing being cut
off as near as possible to cement plug.

8/26/81 Severed 2 3/8" tubing @ 1064'.
Pumped 30 sx. Class H. Cement with 2% CLCH for surface plug.
Set Regulation Dry Hole Marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph Nix TITLE DATE 10-26-81

APPROVED BY Mike Stillfield TITLE Asst. Dir. Conservation DATE 10-26-81

CONDITIONS OF APPROVAL, IF ANY: