

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 80
ARTEZIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gale</i>		Lease <i>Ferguson 84 Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>H</i> <i>1980 N</i> <i>660 E</i>	Section <i>7</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Arb</i>			Type of Equipment <i>Rotary to start 11-18-74</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8</i>	<i>48</i>		<i>400</i>	<i>Circulate</i>
<i>12 1/4</i>	<i>8 5/8</i>	<i>24</i>		<i>1300</i>	<i>"</i>
<i>7 7/8</i>	<i>4 1/2 or 5 1/2</i>	<i>10.5 - 17</i>		<i>8600</i>	<i>250</i>

Casing Data: *2* joints of *22* inch *22* # Grade *22*
(Approved) (Rejected)

Inspected by *[Signature]* date *11-18-74*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required *250*

Type of Shoe used *reamer* Float collar used *2* Btm 3 jts welded *22*

TD of hole *1312* Set *22* Feet of *22* Inch *22* # Grade *22*

New-used csg. @ *12 1/4* with *250* sacks neat cement around shoe *250*
+ *2* sack additives *250*

Plug down @ *12 50* (AM) (PM) Date *11-18-74*

Cement circulated *250* No. of Sacks *250*

Cemented by *[Signature]* Witnessed by *[Signature]*

Temp. Survey ran @ *12 50* (AM) (PM) Date *11-18-74* top cement @ *12 50*

Casing test @ *12 50* (AM) (PM) Date *11-18-74*

Method Used *250* Witnessed by *[Signature]*

Checked for shut off @ *12 50* (AM) (PM) Date *11-18-74*

Method used *250* Witnessed by *[Signature]*

Remarks: *12 50 - 250 - 250 - 250 - 250 - 250 - 250 - 250 - 250 - 250*