

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>David Tasker</u>		Lease <u>Higgins-Cahoon Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>0</u> <u>9903</u> <u>1650 c</u>	Section <u>2</u>	Township <u>18</u>	Range <u>26</u>	County <u>Elky</u>
Drilling Contractor	<u>W Carter Drilling Co.</u>		Type of Equipment <u>Rotary to start 11-18-74</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>30"</u>	<u>20"</u>	<u>91.49</u>		<u>35</u>	<u>48 lb.</u>
<u>17 1/2"</u>	<u>13 7/8"</u>	<u>48</u>		<u>1300 +</u>	<u>1250 surface</u>
<u>12"</u>	<u>8 7/8"</u>	<u>28</u>		<u>1800</u>	<u>250</u>
<u>7 7/8"</u>	<u>4 1/2"</u>			<u>9200</u>	

Casing Data:

Surface 33 joints of 13 3/4" inch 48 # Grade H-40 APT N.
(Approved) (~~Rejected~~)

Inspected by L. G. McManis date 11-21-74

Cementing Program

Size of hole 17 1/2" Size of Casing 13 3/4" Sacks cement required 1040

Type of Shoe used Texas Float collar used 2.50 Btm 3 jts welded

TD of hole 1293 KB Set 1277 1/2 Feet of 13 3/8" inch 48 # Grade H-40

New-used csq. @ 1277 1/2 with 250 sacks neat cement around shoe Class C 2% cc 14.8
+ 800 sack Flowrite additives 130 # 1/2 # Flowrite 2% cc

Plug down @ 6:50 (AM) (PM) Date 11-22-74

Cement circulated 155/54 No. of Sacks 155/54

Cemented by W. J. Anderson Witnessed by L. G. McManis

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 36" hole 600' set 45' KB 20" g. 6 1/2" Ready mix