

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 061702

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoirs.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

APR 15 1975

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface1980' FWL & 1980' FWL Section 8, T-18S, R-29E
Eddy County, New Mexico

7. UNIT AGREEMENT NAME

Hallard Grayburg
San Andres

8. FARM OR LEASE NAME

Tract No. 15

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Loco Hills, Queen
Grayburg San Andres11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

8 - 18S - 29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3531 GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) **Commenced Operations**(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/2" hole 4-1-75. Drilled to 350' KB, set 8 5/8" 28# casing @ 343' KB and cemented with 150 sacks. Let cement set 18 hours and tested to 500 psi. Checked e. k. Cement Weighed 15.6# per gal.

Drilled to 2910', cored 179' to 3089' KB, ran logs, set 4 1/2" casing at 3089' KB and cemented with 400 sacks Class H cement. Cement weighed 15.8# per gal.

Intend to perforate Grayburg and Jackson zones and equip as a producing well.

Will file form 9-330 upon completion.

RECEIVED

APR 14 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Original signed by
J. L. BEEKIN

TITLE

Area Supervisor

DATE

April 11, 1975

(This space for Federal or State office use)

APPROVED BY
COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APR 14 1975
J. L. BEEKIN
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847 - 485

RECEIVED

APR 12 1972

U.S. DEPT. OF THE INTERIOR
BUREAU OF LAND MANAGEMENT