

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-21470
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-4918
7. Lease Name or Unit Agreement Name Turkey State
8. Well No. 1
9. Pool name or Wildcat Turkey Track, SR, QN, GRB, SA
10. Elevation (Show whether DF, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Yates Drilling Company
3. Address of Operator 105 South 4th Street, Artesia, NM 88210
4. Well Location Unit Letter <u>A</u> : <u>330</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>East</u> Line Section <u>32</u> Township <u>18S</u> Range <u>29E</u> NMPM <u>Eddy</u> County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

See attachment.

Post FD-2
11-15-96
P-HA

RECEIVED

OCT - 4 1996

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leckman TITLE Engineering Technician DATE 10-1-96
TYPE OR PRINT NAME _____ TELEPHONE NO. _____

(This space for State Use)

APPROVED BY Mike S. Wakefield TITLE Field Rep. II DATE April 1-97
CONDITIONS OF APPROVAL, IF ANY:

TURKEY STATE #1
Section 32-18S-29E
Eddy County, NM

9-10-96 RUPU

9-12-96 TOH with rods, pump and tubing. Set CIBP at 1900'. Spotted 25 sxs. cement on CIBP, tagged cement at 1530'. Perf. 4 1/2" csg. with 4" - 4 shot - Shot Gun at 370'. Squeezed 75 sxs. Class "C" with 2% CaCl₂. Displaced cement to 370'.

9-13-96 Well on a vacuum. Squeezed with 50 sxs. Class "C" + 4% CaCl₂. Displaced cement to perfs. WOC 3 1/2 hrs. Well still on vacuum.

9-16-96 Notified Ray Smith, NMOCD. Ran bit and scrapper, tagged cement at 368'. Drilled out cement to 370'. Perforated with 4" gun at 870', ran 4 1/2" packer, set at 620'. Squeezed with 75 sxs. Class "C" + 2% CaCl₂. WOC 4 hrs. Pressured up cement plug to 800#, held okay. Tagged cement at 705'. Witnessed by NMOCD.

9-17-96 Cut off wellhead, cut 4 1/2" csg. at 370'. Pulled and laid down 370' 4 1/2" csg.
Spotted 25 sxs. Class "C" + 2% CaCl₂ at 420', could not tag cement.
Spotted 25 sxs. Class "C" from 300-250'

9-18-96 TIH, could not tag cement.
Spotted 25 sxs. Class "C" + 2% CaCl₂ from 300-225', tagged cement at 315'.
Spotted 30 sxs. Class "C" + 2% CaCl₂ from 315'-215', tagged cement at 239'.
Spotted 14 bbls. plug mud from 239' - to surface.
Spotted 15 sxs. Class "C" cement from 50' - surface.

Erected surface marker.