

NO.	COPIES RECEIVED	3
	DISTRIBUTION	
		1
		1
		1
	OFFICE	
	FOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUN 4 1975

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Atlantic Richfield Company ✓		5. State Oil & Gas Lease No.
3. Address of Operator P. O. Box 1710, Hobbs, New Mexico 88240		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>7</u> TOWNSHIP <u>18S</u> RANGE <u>27E</u> NMPM.		8. Farm or Lease Name Stirling Com.
15. Elevation (Show whether DF, RT, GR, etc.) 3285.5' GR		9. Well No. 1
		10. Field and Pool, or Wildcat Red Lake Penn Gas
		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒ Surf & Intermediate
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17 1/2" hole @ 6:00 PM 5/20/75. Drld 37', set 25' of 20" conductor pipe @ 37' & cmt'd w/7 yds of Readi-mix cont'g 2% CaCl to surface. Drld 12 1/2" hole to 892'. Ran 13-3/8" OD 48# H-40 csg w/GS & FC. Set csg @ 890' & cmt'd w/475 sx Cl C w/4% gel, 5# Kolite & 2% CaCl followed by 275 sx Cl C, 2% CaCl. Circ to surface. WOC 21 1/2 hrs. Press tstd csg & BOP to 600# for 30 mins, OK. Commenced drlg 11" hole 5/24/75. Drld 11" hole to 1900'. Ran 44 jts (1886') of 8-5/8" OD 24# K-55 ST&C csg & set @ 1900'. FC @ 1820'. GS @ btm. Cmt'd w/570 sx Cl C w/4% gel, 5# Kolite & 2% CaCl/sk followed by 240 sx Cl C w/2% CaCl. Circ. to surface. WOC 37 hrs. Drld cmt & float equip 1334-1900'. Press tstd 8-5/8" OD csg & BOP to 2000# for 30 mins. No press drop. OK. Commenced drlg 7-7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge.

SIGNED 

TITLE Dist. Drlg. Supv.

5/30/75

APPROVED BY 

TITLE SUPERVISOR, DISTRICT II

DATE JUN 4 1975

CONDITIONS OF APPROVAL, IF ANY: