Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT	
P.O. Box 1980, Hobbs, NM	88240

OIL CONSERVATION DIVISION

WELL API NO.	
--------------	--

P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088	RECEIVED WELL API NO.			
- V-V	9 1 30-015-21532			
DISTRICT II Santa Fe, New Mexico 8 P.O. Drawer DD, Artesia, NM 88210	STATE FEE X			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	APR 16 '90 6. State Oil & Gas Lease No.			
SUNDRY NOTICES AND REPORTS ON WELI	LS CLE D.			
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF DIFFERENT RESERVOIR. USE "APPLICATION FOR PER (FORM C-101) FOR SUCH PROPOSALS.)	OR PLOT BASK TO A 7. Lease Name or Unit Agreement Name			
1. Type of Well: OIL GAS WELL X OTHER	Spencer ADE Com			
2. Name of Operator	8. Well No.			
YATES PETROLEUM CORPORATION				
3. Address of Operator	9. Pool name or Wildcat			
105 South 4th St., Artesia, NM 88210	Undes. Canyon			
4. Well Location				
Unit Letter K: 1650 Feet From The South	Line and 1980 Feet From The Line			
Section 1 Township 18S Ran	nge 26E NMPM Eddy County			
10. Elevation (Show whether I	DF, RKB, RT, GR, etc.)			
Check Appropriate Box to Indicate N	Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB			
OTHER:	OTHER: Plugback, perforate & treat			
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
1-18-90. MIRU. Set CIBP 8650' and cap w/35' cement. Perforated 8281-8417' w/18 .42" holes as follows: 8281, 82, 83, 92, 93, 8300, 01, 02, 03, and 8304' (10 holes); 8417, 18, 19, 20' (8 holes-2 SPF). Acidized perforations w/1500 gals 15% NEFE acid. Swabbed well. 1-23-90. RBP set below 7721' and tested to 2000 psi. WIH and perforated 7693-7721' w/13 .42" holes as follows: 7693, 94, 95, 96, 97 and 7714, 15, 16, 17, 18, 19, 20 and 7721'. 1-24-90. Acidized perforations 7693-7721' w/1500 gals 15% NEFE acid. 1-26-90. Swabbed dry.				

I hereby certify that the inform	nation above is true and complete to the best of my knowle	dge and belief.	
TOWATTER ALAS	nota Sandlein	dge and beliefProduction_Supervisor	DATI!
TYPE OR PRINT NAME	Juanita Goodlett		TELEPHONE NO. 505/748-147
(This space for State Use)	ORIGINAL SIGNED BY MIKE WILLIAMS		APR 1 7 1990
APPROVED BY	SUPERVISOR, DISTRICT IT	TITLE	DATI!