

RECEIVED BY

FEB 28 1985

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYBrewer DD  
Alameda, NM 88210

LEASE

NM - 01159

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nelson

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Loco Hills (Queen, Grayburg, SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 4, T-18-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
KB 3573.6', GL 3567.6'

## SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA OFFICE  
Use Form 9-331-C for such proposals.)1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

BelNorth Petroleum Corporation

3. ADDRESS OF OPERATOR One Petroleum Center

Building 6, Suite 201 Midland, Texas 79705

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FWL &amp; 330' FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: 990' FWL &amp; 330' FNL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☒

(other)

FEB 15 1985

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. RIH with tubing to TD 3494' and set cement plug across perms and across San Andres and Grayburg bringing cement up to 2550' across tie end of 4" liner and 5-1/2" casing and tag plug.
2. Perf at base of salt 1200' and squeeze cement 100' in and 100' out of 5-1/2" casing. Tag.
3. Perf at top of salt 530' and squeeze cement 100' in and 100' out of 5-1/2" casing. Tag plug.
4. 50' plug at surface in 5-1/2" casing and set P&A marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED L. W. Helms, Jr. TITLE Drilling Engineer DATE 2-14-85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:TITLE Drilling Engineer DATE 2-26-85