

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED
FEB 4 1980

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Exxon Corporation
3. ADDRESS OF OPERATOR
P. O. Box 1600, Midland, TX 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 810' FWL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	

5. LEASE
LC-069274
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Red Lake Fed. Com.
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 6, T-18-S, R-27-E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GR 3388

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Released packer and circ hole with 9.5# mud laden fluid
- Pull tubing and packer.
- Set CIBP in 4 1/2" csg at 7100', cap w/4 sx of cmt, top of cmt 7050'.
- Circ hole w/9.5# mud laden fluid. Spot 25 sack plug from 5845-6000'
- Spot 25 sack plug from 3975-4150'.
- Spot 25 sack plug from 1950-2100'.
- Spot 25 sack plug from surface to 150'.
- Removed wellhead install well marker.
- Plugged and abandoned 8-31-78.
- Form 9-331 will be forwarded when USGS and B.L.R. requirements are complied with.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED George H. Stewart TITLE Unit Head

DATE 9-27-78

(Orig. Sgd.) GEORGE H. STEWART (This space for Federal or State office use)
ACTING DISTRICT ENGINEER

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: