

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp.</u>		Lease <u>Dayton EZ</u>		Well # <u>1</u>	
Location of Well	Unit/H <u>2310 N</u> <u>330 E</u>	Section <u>21</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Byrd Drilling Co.</u>		Type of Equipment <u>Rotary</u>		
<i>* Witness</i> <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 3/4"</u>	<u>32</u>		<u>400</u>	<u>line</u>
<u>9 1/2"</u>	<u>7"</u>	<u>20</u>		<u>1240</u>	<u>line</u>
<u>6 1/4"</u>	<u>4 1/2" + 5 1/2"</u>	<u>9.5 + 15.55</u>		<u>1800</u>	<u>150</u>
Casing Data:					
Size <u>32</u> joints of <u>7</u> inch <u>20</u> # Grade <u>None</u> <u>8 1/2</u> <u>STC</u> (Approved) (Rejected)					
Inspected by <u>James R. Gorton</u> date <u>1-8-75</u>					
Cementing Program					
Size of hole <u>9 1/2</u> Size of Casing <u>7</u> Sacks cement required <u>270</u>					
Type of Shoe used ^{Horse TEXAS TYPE} MADE Float collar used <u>None</u> Btm 3 jts welded <u>THROD LOK</u>					
TD of hole <u>1200</u> Set <u>1230.30</u> Feet of <u>7</u> Inch <u>20</u> # Grade <u>K 55</u> <u>STC</u> <u>R 3</u>					
New-used csg. @ <u>1200</u> ft with <u>150</u> sacks neat cement around shoe <u>28</u> ft					
+ <u>350</u> sax <u>mix. 8 1/2</u> additives <u>410</u> <u>ft</u> <u>1 1/2</u> <u>STC</u>					