

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPER OR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 16 1975

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p>SUNDRY NOTICES AND REPORTS ON WELLS. O.C.C. <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small></p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> <input checked="" type="checkbox"/> For</p>
<p>1. Name of Operator Yates Petroleum Corporation</p>		<p>5. State Oil & Gas Lease No.</p>
<p>2. Address of Operator 207 South 4th Street - Artesia, NM 88210</p>		<p>7. Unit Agreement Name</p>
<p>3. Location of Well UNIT LETTER H 2310 FEET FROM THE North LINE AND 330 FEET FROM East 21 LINE, SECTION 18S RANGE 26E NMPM.</p>		<p>8. Farm or Lease Name Dayton "EZ"</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 3353' GR</p>		<p>9. Well No. 1</p>
<p>12. County Eddy</p>		<p>10. Field and Pool, or Wildcat Atoka (S.A.)</p>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of completion if any proposed work) SEE RULE 1103.

Spudded a 15" hole at 5:00 PM 12-5-75.
 TD 416' - Ran 9 joints of 10-3/4" 32# K-55 new casing 408' set at 403' KB. Cemented w/250 sacks of Class "C" 4% CaCl. PD 8:00 AM 12-7-75. Cement circulated. WOC 12 hours, reduced hole to 9 1/2" and drilled plug and resumed drilling.
 TD 1200' - Ran 29 joints of 7" 20#, K-55 new casing (1182') set at 1200'. Cemented w/350 sacks of Incor mix (6% gil + 0.6% flocele 2% CaCl) + 150 sacks of Class "C" 2% CaCl. PD 1:30 PM 12-8-75. Cement circulated. WOC. Cement fell and filled hole w/3 1/4 yards of Ready-mix. WOC 18 hours, backed off landing joint and nipples up, tested BOP's to 1000#. OK. Drilled shoe and tested casing to 600#. OK. Reduced hole to 6 1/2" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tornblom TITLE Geol. Secty DATE 12-13-75
 APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE DEC 16 1975
 CONDITIONS OF APPROVAL, IF ANY: