

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JAN 13 1976

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Well State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Dayton "EY"
3. Address of Operator 207 South Fourth Street - Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.		10. Field, Pool, or Wildcat Atoka S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3370' GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Spudded a 15" hole at 3:00 PM 12-28-75. Drilled to 426' and ran 11 joints of used 10-3/4 32# casing (435') set at 426' KB. Cemented w/200 sacks of Class "C" 4% CaCl. PD 2:30 AM 12-29-75. WOC 12 hours cut off casing, drilled plug and reduced hole to 9 1/2" and resumed drilling. TD 1210'. - Ran 31 joints of used 7" 23# LT&C (1222') casing, 1-Tex-Pattern shoe, centralizer at 1171' and basket at 615 & 530' set at 1210' and cemented by Denton w/350 sacks of mix 2% CaCl, followed w/150 sacks of Class "C" 2% CaCl. PD 5:00 PM 12-31-75. Cement circulated. WOC and cement dropped 100' in annulus. Filled hole w/3 yards of Ready-Mix, in place at 6:00 AM 1-1-75. WOC 18 hours, nipples up, installed BOP's and tested to 1000#. OK. Drilled plug and tested casing to 600#. OK. Reduced hole to 6 1/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlin TITLE Geol. Secty DATE 1-12-76

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JAN 13 1976

CONDITIONS OF APPROVAL, IF ANY: