

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER ED
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Jake Petr. Corp.</u>		Lease <u>Payton ER</u>		Well # <u>2</u>	
Location of Well	Unit <u>I</u> <u>16505</u> <u>3302</u>	Section <u>21</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Byrd Drilling Co.</u>		Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15"</u>	<u>10 3/4"</u>	<u>32</u>		<u>400</u>	<u>line</u>
<u>9 1/2"</u>	<u>7"</u>	<u>20</u>		<u>1240</u>	<u>line</u>
<u>6 1/4"</u>	<u>4 1/2" x 5 1/2"</u>	<u>9.5 + 15.5</u>		<u>1800</u>	<u>150</u>
Casing Data:					
Surface <u>30</u> joints of <u>7</u> inch <u>20</u> # Grade <u>GPI A-55</u>					
(Approved) (Rejected)					
Inspected by <u>W. E. Miller</u> date <u>12-13-75</u>					
Cementing Program					
Size of hole <u>3 1/2"</u> Size of Casing <u>7</u> Sacks cement required <u>500</u>					
Type of Shoe used <u>Annular</u> Float collar used <u>None</u> Btm <u>2</u> jts welded <u>Thread Lock</u>					
TD of hole <u>1195</u> Set <u>1152</u> Feet of <u>7</u> Inch <u>20</u> # Grade <u>55</u>					
New-used csg. @ <u>1182</u> with <u>150</u> sacks neat cement around shoe, <u>Class 80</u>					
+ <u>330</u> sack <u>additives</u> <u>6 1/2" x 1 1/2" 4% / 100</u>					
Plug down @ <u>10:30</u> (AM) (PM) Date <u>12-13-75</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>75</u>					
Cemented by <u>Tom</u> Witnessed by <u>W. E. Miller</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>Surface 15" hole Run 1140 10 3/4" 32" line</u>					
<u>W. 412 KG 32" 399' 32" Out 250/40 2000</u>					
<u>PD 5:30 PM. Run 15 1/4" lost zone 273' but got it back</u>					
<u>W. 412 73-400 2 1/2" 270' 1060-1091</u>					