

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS, AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Bone Spring	7980	8075	DST #1 Op 15 min wk blow. SI 90 min. op 1 hr. v wk blow air. Rec. 90' DF IHP 3611 IFF 87 ISIP 368 FFP 105 FSIP 263 FHP 3611
Cisco	9588	9640	DST #2 Op 15 min. v wk blow. SI 90 min. Op 2 hr. v wk blo. Rec. 438' SW IHP 4289, IFF 88, ISIP 2190 FFP 264 FSIP 681, FHP 4850
Morrow	11365	11430	DST #3 Op 15 min. v wk blow, SI 90 min. Op 2 hr dead. Rec. 1500' WC & 10' DM. IHP 5886, IFF 664, ISIP 1394, FFP 686, FSIP 1394, FHP 5886
Morrow	11465	11611	DST #4 Op 15 min. v wk blow. SI 90 min. Op 2 hr. v wk blow increased to strong blow. Rec. 1560' WC 155' DM. No show. IHP 5954, IFF 860, ISIP 3797, FFP 860, FSIP 4512, FHP 5912.
Morrow	11605	11617	DST #5 Op 30 min strong blow unloaded WC @ 120# on 3/8" ck. SI 5 hr. Op 1 hr GTS immediately 1/4" ck 3500 psi. Sampler 8.52 ft. 3 gas @ 600 psi. IHP 6502, IFF 4588, ISIP 4827, FFP 4252, FSIP 4518, FHP 6450

See attached sheet

38. GEOLOGIC MARKERS

NAME	MEAS. DEPTH	TOP	TRUE VERT. DEPTH
Rustler	425		425
Yates	1693		1693
Queen	2747		2747
San Andres	3540		3540
Bone Spring	4985		4985
Wolfcamp	8760		8760
Cisco	9589		9589
Strawn	10611		10611
Atoka	11018		11018
Morrow	11250		11250
Chester	11680		11680

6450

871-233