

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAR 9 1976

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

B. C. C.

ARTESIA, OFFICE

5a. Indicate Type of Well Date <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm & Lease Name Dayton "FT"
9. Well No. 1
10. Field, Pool, or Wildcat Und Atoka S.A.
12. County Eddy

1. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER M 330 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 18S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3411' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ENTERING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG & ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in case of proposed work) SEE RULE 1103.

Spudded a 9½" hole at 1:30 PM 2-25-76.

TD 1200' - Ran 28 joints of 7" 20# K-55 ST&C (1204.01') set at 1200' KB. Centralizers at 1155 and 519', baskets at 566 and 475'. Cemented by Denton w/350 sacks of Lite + 2% CaCl. Cement circulated. PD 7:15 AM 2-27-76. WOC 18 hours nipples up, installed BOPs. and tested to 1000#. OK. Drilled plug and tested casing to 600#. OK. Reduced hole to 6½" and resumed drilling.

TD 1786'; PBTD 1780'. Ran 21 joints of 4½" 9.5# J-55 (769') and 25 joints of 5½" 15.5# J-55 (1009') (46 joints 1778') set at 1780'. 5 centralizers at 1745, 1705, 1665, 1625 and 1685' and 1-Guide shoe, cemented w/175 sacks of Class "C" cement. Cement circulated. PD 4:30 PM 3-2-76. WOC and tested to 1000#. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty 3-8-76

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE MAR 11 1976

CONDITIONS OF APPROVAL, IF ANY: