

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 23 1976

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Dayton "FY"
9. Well No. 1
10. Field, Pool, or Wildcat Und. Atoka (S. A.)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT DEPTH OR TO USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

ARTESIA OFFICE

1. Name of Operator Yates Petroleum Corporation✓
2. Address of Operator 207 So. 4th Street-Artesia, NM 88210
3. Location of Well UNIT LETTER <u>L</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>21</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.
15. Elevation (Show whether DF, RT, GP, etc.) 3403' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set Prod. csg, Perf, & Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated cost of work) SEE RULE 1103.

TD 1775'; PBTD 1714'. Ran 26 joints of 4½" 10.5# H-55 (761') and 23 joints of 5½" 15.5# J-55 (951') (49 joints 1712') set at 1714'. 5 centralizers at 1584, 1558, 1533, 1508 and 1481'. 1-Guide shoe. Cemented w/175 sacks of Class "C" cement. Cement circulated. PD 3:45 PM 4-18-76. WOC and tested to 1000#. OK. 53  
Perforated 1533-1651 w/27 .45" shots as follows: 1st Stage - 1553, 67, 86, 88, 90, 92, 94, 96, 98, 1600, 29, 50 (12 shots). Acidized w/3000 gallons of 15% regular acid. 2nd Stage: - 1554½, 62, 70, 85, 87, 89, 91, 93, 95, 97, 99, 1601, 27, 31 and 51' (15 shots). Treated all perforations w/60000 gallons of treated water and 90000# 20-40 sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson

TITLE Geol. Secty

4-22-76

APPROVED BY W. A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE APR 23 1976

CONDITIONS OF APPROVAL, IF ANY: